

Other Fire Protection Products | Waterflow Alarm Indicators (Vane Type) | [Waterflow Detectors, Vane Type](#)

Model WFD-V

Product Description

Model WFD-V

2 through 8 in. NPS have a rated working pressure of 450 psi (3105 kPa). Two snap switches and pneumatic retard.

Approved for Schedule 10 and 40 pipe.

Product Specification

| Model No | Valve Size | |
|-------------|------------|---------|
| | mm | (in) |
| WFD-V-2 | 50 | (2) |
| WFD-V-2 1/2 | 65 | (2 1/2) |
| WFD-V-3 | 80 | (3) |
| WFD-V-4 | 100 | (4) |
| WFD-V-6 | 150 | (6) |
| WFD-V-8 | 200 | (8) |

Contacts rated for 10.1 A at 125/250 VAC, 2.0 A at 24 VDC. The operating temperature range is 40°F to 120°F (4.5°C to 49°C).

Details

| | |
|---------------------------|--|
| Category | Waterflow Detectors, Vane Type |
| Class of Work | 1042 - Waterflow Detectors(vane type) |
| Approval Standard | FM 1042 - Vane-Type Waterflow Alarm Indicators |
| Certification Type | FM Approved |
| Listing Country | Hong Kong |

Company

Fivalco Ltd

1301 Bank of America Tower, 12
Harcourt Road, Central, Hong
Kong

<http://fivalcovalves.com>